

PE tarpaulin Standard FR

STANDARD 140 GR/M²

Flame-retardant PE tarpaulins provide safe protection against fire in various applications including events, construction, and industry. These durable and reliable tarps meet fire safety standards, offering peace of mind in critical situations.



■ Technical data

Tensile strength	857N / 5cm (ISO 13937-1)
Tear strength	187N / 5cm (ISO 13937-1)
Temperature resistance	-40°C / +80°C

■ Product information

- HDPE tape fabric with LDPE coating on both sides
- Welded hem all round with PP rope reinforcement and an aluminium eyelet every metre, inner Ø 12mm
- Each product fitted with a sewn-in label
- Each tarpaulin packed in a transparent PE bag with a neutral COVER insert sheet, 4 languages and EAN code
- Outer packaging in sturdy boxes of 5-ply water-resistant cardboard
- Delivered on Euro pallets (80 × 120cm)
- Pallet height: half approx. 125cm, full approx. 210cm

■ Customisation

- Custom size: small quantities, delivery time from approx. 3-4 months
- Custom colour and/or weight: minimum order approx. 35,000m², delivery time 3-4 months
- Private label / own brand packed in box or bale
- This product can be printed
- Optional: VCI anti-corrosion method actively protects your metal against rust (VpCI)
- Optional: CORONA surface treatment gives printed texts more durable adhesion

Sizes

Finished size (m)	 White	Quantity per box	Quantity per half pallet	Quantity per full pallet
2 × 3	✓	20	400	560
3 × 4	✓	10	200	280
4 × 6	✓	4	96	144
6 × 8	✓	3	48	72
8 × 10	✓	1	28	40
10 × 12	✓	1	16	28